# CLASSIFICATION CHANGE

12 .

To UNCLASSIFIED

By authority of GOS Changed by Shirley

Classified Document Master Control Station, NASA Scientific and Technical Information Facility

SID 62-208

BOILERPLATE NUMBER 4, COMMAND MODULE WATER IMPACT TEST SPECIFICATION PROJECT APOLLO SPACECRAFT (Unclassified)



28 February 1962

Approved By

Vice President and Apollo Program Manager


the national defense of the me Espionage Laws, Title 18 U.S.C. or revelation of its contents in any

NORTH AMERICAN AVIATION, INC. SPACE and INFORMATION SYSTEMS DIVISION



### CONTENTS

Paragraph	Title								Page
1.	SCOPE			•			•	•	1
1.1	Scope	•	•	•	•	•	•	•	1
2.	APPLICABLE DOCUMENTS .						•		1
2.1	General	•	•	•	•	•	•	•	1
3.	REQUIREMENTS						•		1
3. 1	General	•	•		•				1
3. 2	Components	•							1
3, 2, 1	Boilerplate Sections							•	1
3. 2. 1. 1	Cabin Section		•						1
3. 2. 1. 1. 1	Cabin Housing								3
3. 2. 1. 1. 2	Main Hatch								3
3. 2. 1. 1. 3	Restraint and Support	Equ							3
3. 2. 1. 1. 4	Authropomorphic Dum								3
3. 2. 1. 1. 5	On Board Instrumenta								3
3. 2. 1. 1. 5.				•					3
3. 2. 1. 1. 5.									3
3. 2. 1. 1. 5.									3
3, 2, 1, 1, 6	Parachute Bridle Atta							•	4
3. 2. 1. 1. 7	Air-Lock						•	•	4
3. 2. 1, 2	Lower Compartment .						•	•	4
3. 2. 1. 2. 1	Impact Attenuation Ba								4
3. 2. 1. 2. 2	Pillow Type Impact At	_						•	4
3. 2. 1. 2. 3					_			•	4
3. 2. 2	•					•	•	•	4
3. 3			•	•		•	•	•	4
3, 3, 1	_				•	•	•	•	4
3. 4			•		•	•	•	•	4
3. 4. 1		•			•			•	4
3, 4, 2	W-1-14		•	•		•	•	•	5
3. 4. 2. 1	G	•	•	•	•	•	•	•	_
3. 4. 2. 1	Center of Gravity	•	•	•	•	•	•	•	5
•	Heat Shielding Simulation	•	•	•	•	•	•	•	5
3. 4. 4	Attachment	•	•	•	•	•	•	•	5
3. 4. 5	Water Protection.	•	•	•	•	•	•	•	5
3. 5	Ground Support Equipment .							•	5
3.5.1	Ground Handling Equipment								5





CONFIDE



### CONTENTS (Cont'd)

Paragraph	Title	Page								
4.	QUALITY ASSURANCE PROVISIONS									
4. 1	General	. 5								
4.2	Inspection and Tests	. 5								
5.	PREPARATION FOR DELIVERY	. 5								
5. 1	Airborne Equipment	. 5								
5. 2	Transportation	. 5								
6.	NOTES	. 5								
6. 1	Definitions	. 5								





#### **APPENDICES**

Appendix													Page
I-A	Contractor-Furnished Equipment, Contractor-												
	Installed	•	•	•	•	•	•	•	•	•	•	•	6
			ILI	LUST	TRAT	rion	S						
Figure													Page
1	Boilerplate	Num	nber	4.									2





#### 1. SCOPE

1.1 Scope. - This specification covers requirements for the Command Module Water Impact Test Boilerplate. The boilerplate shall be used to test the earth impact attenuation system and crew shock absorption system of the command module.

#### 2. APPLICABLE DOCUMENTS

2.1 General. - The following documents shall form a part of this specification.

#### Government Documents

#### Air Force

ARDCM-80-1,

Handbook of Instructions for Aircraft

Volume 1

Designers

#### National Aeronautics and Space Administration

NCP200-2

Quality Assurance Provisions for Space Contractors, dated 15 December 1961

# Space and Information Systems Division, North American Aviation, Inc.

SID 62-240

Preparation for Delivery of Airborne Equipment, General Requirements for

#### 3. REQUIREMENTS

3. l General. - The configuration of the Command Module Water Impact Test Boilerplate shall be similar to the configuration of the prototype command module. The boilerplate configuration is shown in Figure 1.

#### 3.2 Components. -

- 3.2.1 Boilerplate Sections. The Command Module Water Impact Test Boilerplate shall consist of a cabin section and a lower compartment (Ref. Fig. 1).
- 3.2.1.1 Cabin Section. The Cabin Section of the boilerplate shall include the following:



### CONPRESENTAL





Figure 1. Boilerplate Number 4



- (a) Cabin housing
- (b) Main watch
- (c) Restraint and support equipment
- (d) Anthropomorphic dummies (with test instruments)
- (e) On board instrumentation
- (f) Parachute bridle attach points
- (g) Air-Lock
- 3.2.1.1.1 Cabin Housing. The cabin housing of the boilerplate shall be similar to the cabin housing of the prototype command module.
- 3.2.1.1.2 Main Hatch. The main hatch of the boilerplate shall provide ingress and egress for personnel.
- 3.2.1.1.3 Restraint and Support Equipment. The restraint and support equipment for the dummies shall be similar to the crew restrain and support equipment of the prototype command module.
- 3.2.1.1.4 Anthropomorphic Dummies. The anthropomorphic dummies used in the boilerplate shall be instrumented with testing equipment.
- 3.2.1.1.5 On Board Instrumentation. The on board instrumentation in the boilerplate shall include:
  - (a) Seven pressure transducers (Bridge Type)
  - (b) 27 accelerometers (Bridge Type)
  - (c) Strain gauges, as required
- 3.2.1.1.5.1 Pressure Transducers. The pressure transducers shall record the impact of the water on the impact attenuation bags.
- 3.2.1.1.5.2 Accelerometers. The accelerometers shall be used to record the forces on the shock absorption equipment during testing.
- 3.2.1.1.5.3 Strain Gauges. The strain gauges shall be used to record lateral and transverse strains on the boilerplate during testing.





### CONFIDENTIAL

- 3.2.1.1.6 Parachute Bridle Attach Points. Parachute bridle attach points shall be used to support the boilerplate in the test stand (Ref. Fig. 1).
- 3.2.1.1.7 Air Lock. The air lock of the command module shall be simulated in the cabin section of the boilerplate.
- 3.2.1.2 <u>Lower Compartment.</u> The lower compartment of the boilerplate shall not be affected by water. The lower compartment shall include the impact attenuation system. The impact attenuation system shall include:
  - (a) Seven impact attenuation bags
  - (b) Four pillow type impact attenuation bags
  - (c) Tension straps, as required
- 3.2.1.2.1 <u>Impact Attenuation Bags.</u> The boilerplate shall contain seven impact attenuation bags. The impact attenuation bags shall be located around the inside perimeter of the lower compartment as shown in figure 1.
- 3.2.1.2.2 Pillow Type Impact Attenuation Bags. Four pillow type impact attenuation bags shall be installed in the lower compartment of the boilerplate. The arrangement of the bags shall be as shown in figure 1.
- 3.2.1.2.3 <u>Tension Straps</u>. Tension Straps shall be installed in the lower compartment of the boilerplate to aid in the support of the large attenuation bags. (Ref. Fig. 1)
- 3.2.2 Equipment. The equipment for the boilerplate shall include the equipment listed in Appendix I-A.

#### 3.3 Performance. -

3.3.1 General. - The water impact of the prototype command module shall be simulated in the test of the boilerplate. The water impact landing shall be recorded by a motion picture camera. The boilerplate shall be capable of withstanding at least 15 test drops.

### 3.4 Design and Construction. -

3.4.1 General. - The boilerplate shall be constructed of the materials necessary to insure structural soundness and stiffness with respect to impact absorption. ARDCM-80-1, Volume 1, shall be used for guidance and reference material in the design and construction of the boilerplate.





### CONFIDENTIAL

- 3.4.2 Weight. The boilerplate shall have a mass and center of gravity similar to the mass and center of gravity of the prototype command module.
- 3.4.2.1 Center of Gravity. The center of gravity of the boilerplate shall be placed to give the boilerplate an impact angle of minus 15 degrees forward, when the crew is in the feet forward position.
- 3.4.3 <u>Heat Shielding Simulation</u>. The boilerplate shall not contain heat shielding. The stiffness of the heat shielding of the command module shall be simulated in the boilerplate.
- 3.4.4 Attachment. The cabin section and lower compartment section of the boilerplate shall be joined by retaining straps, as required.
  - 3.4.5 Water Protection. The boilerplate shall be watertight.
  - 3.5 Ground Support Equipment. -
- 3.5.1 Ground Handling Equipment. Ground Handling Equipment shall be required to transport, demonstrate and test the boilerplate. The requirements for Ground Handling Equipment are not part of this specification.

#### 4. QUALITY ASSURANCE PROVISIONS

- 4.1 General. Quality Assurance Provisions for the boilerplate shall be in accordance with the applicable portions of NASA Bulletin NCP200-2.
- 4.2 <u>Inspection and Tests.</u> Inspections and tests to determine conformance of the boilerplate to contract and specification requirements shall be conducted prior to delivery to the test site.

#### 5. PREPARATION FOR DELIVERY

- 5. l Airborne Equipment. Airborne equipment shall be prepared for delivery in accordance with Specification SID 62-240.
- 5.2 <u>Transportation</u>. The boilerplate shall be delivered to the local area testing site by the contractor.

#### 6. NOTES

6.1 <u>Definitions</u>. - A boilerplate is a simulated spacecraft module for pre-developmental and/or developmental tests leading to the design of a prototype module.





### Appendix I-A

# Contractor-Furnished Equipment, Contractor-Installed

TATION	Part No.			
COMMUNICATIONS AND INSTRUMENTATION	Description	Pressure Transducers (Bridge Type)	Accelerometers (Bridge Type)	Strain Gauges
SI	Quantity	٢	72	
	Item No.	-	2	٣



### Appendix I-A

# Contractor-Furnished Equipment, Contractor-Installed

	Part No.		
CREW SYSTEM	Description	Anthropomorphic Dummies	Restraint and Support Equipment (seats)
	Quantity	m	<b>e</b>
	Item No.	1	2





### Appendix I-A

### Contractor-Furnished Equipment Contractor-Installed

	Part No.			
STRUCTURES	Description	Large Impact Attenuation Bags	Pillow Type Impact Attenuation Bags	Tension Straps
	Quantity	7	4	
	Item No.	1	. 2	ĸ